

Robotics-Kit Kassow



PRODUCT INFORMATION

Sets specially designed for cable routing on Kassow robots.


The assembly includes the protective hose, end sleeves and the appropriate fastening with non-slip hook-and-loop tape. For an easier installation of pre-assembled cables, the protective conduit is available in slotted LS.

The set offers a lowest possible interference contour for a low risk of damage.

Optional accessories:

- K KU-Fix - hook-and-loop tape sili-cone-free
- KBM 840 - metal cable ties

SPECIFICATIONS



Type	Order No.	Colour	MOQ qty.
FHS-UHE-Set Kassow 1205	83693514	Black / Red	1
Set consists of: 2m EWX-PP-LS M32/P29, 4x FHS-UHE incl. Velcro tape, 2x end grommet, 1x wire insertion tool			



RoHS (EC Directive 2011/65/EU)



ROBI approval

All details given in our sales brochures and catalogues, as well as the information available online, are based on our current knowledge of the products described.

The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the product described.

A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information.

All information with respect to the chemical and physical properties of Murrplastik products, as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge.

They do not release the buyer from the obligation to carry out his own tests and trials in order to determine the concrete suitability of the products for the intended purpose.

Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility for the quality of this information.

Murrplastik accepts no liability for damage caused as a result of using our products.

Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services.

Our General Terms and Conditions apply.